



CERTIFIED SOLAR COLLECTOR

SUPPLIER:
Dimas SA
 2nd KLM Argos-Nafplion
 Argos, 21200 Greece
 www.dimas-solar.gr
 In Accordance with:
SRCC Standard 100-2010-08

BRAND: Dimas SA
 MODEL: SOL+23
 COLLECTOR TYPE: Glazed Flat Plate
 CERTIFICATION #: 2011077C
 Original Certification: October 19, 2011
 Expiration Date: April 11, 2023

The solar collector listed below has been evaluated by the Solar Rating & Certification Corporation™ (SRCC™), an ISO/IEC 17065 accredited and EPA recognized Certification Body, in accordance with SRCC OG-100, Operating Guidelines and Minimum Standards for Certifying Solar Collectors, and has been certified by the SRCC. This award of certification is subject to all terms and conditions of the Program Agreement and the documents incorporated therein by reference. This document must be reproduced in its entirety.

COLLECTOR THERMAL PERFORMANCE RATING							
Kilowatt-hours (thermal) Per Panel Per Day				Thousands of Btu Per Panel Per Day			
Climate ->	High Radiation (6.3 kWh/m ² .day)	Medium Radiation (4.7 kWh/m ² .day)	Low Radiation (3.1 kWh/m ² .day)	Climate ->	High Radiation (2000 Btu/ft ² .day)	Medium Radiation (1500 Btu/ft ² .day)	Low Radiation (1000 Btu/ft ² .day)
Category (Ti-Ta)				Category (Ti-Ta)			
A (-5 °C)	9.8	7.4	5.1	A (-9 °F)	33.5	25.4	17.3
B (5 °C)	9.0	6.6	4.2	B (9 °F)	30.6	22.4	14.3
C (20 °C)	7.6	5.3	3.0	C (36 °F)	26.0	18.1	10.2
D (50 °C)	5.3	3.1	1.1	D (90 °F)	18.2	10.6	3.6
E (80 °C)	3.3	1.4	0.0	E (144 °F)	11.3	4.6	0.1

A- Pool Heating (Warm Climate) B- Pool Heating (Cool Climate) C- Water Heating (Warm Climate)
D- Space & Water Heating (Cool Climate) E- Commercial Hot Water & Cooling

COLLECTOR SPECIFICATIONS					
Gross Area:	2.239 m ²	24.10 ft ²	Dry Weight:	35 kg	77 lb
Net Aperture Area:	2.033 m ²	21.88 ft ²	Fluid Capacity:	1.8 liter	0.5 gal
Absorber Area:	1.976 m ²	21.27 ft ²	Test Pressure:	2400 kPa	348 psi

TECHNICAL INFORMATION			Tested in accordance with:		
ISO Efficiency Equation [NOTE: Based on gross area and (P)=Ti-Ta]					
SI UNITS:	$\eta = 0.711 - 3.49780(P/G) - 0.00350(P^2/G)$	Y Intercept:	0.714	Slope:	-3.747 W/m ² .°C
IP UNITS:	$\eta = 0.711 - 0.61646(P/G) - 0.00034(P^2/G)$	Y Intercept:	0.714	Slope:	-0.660 Btu/hr.ft ² .°F

Incident Angle Modifier								Test Fluid:	
θ	10	20	30	40	50	60	70	Water	
K_{ra}	1.00	0.99	0.98	0.96	0.93	0.87	0.76	Test Mass Flow Rate:	0.0192 kg/(s m ²) 14.17 lb/(hr ft ²)
Impact Safety Rating:									

REMARKS:

Jeri Higgins

Technical Director





CERTIFIED SOLAR COLLECTOR

SUPPLIER:
Dimas SA
 2nd KLM Argos-Nafplion
 Argos, 21200 Greece
 www.dimas-solar.gr
 In Accordance with:
SRCC Standard 100-2010-08

BRAND: Dimas SA
MODEL: SOL+23
COLLECTOR TYPE: Glazed Flat Plate
CERTIFICATION #: 2011077C
Original Certification: October 19, 2011
Expiration Date: April 11, 2023

The solar collector listed below has been evaluated by the Solar Rating & Certification Corporation™ (SRCC™), an ISO/IEC 17065 accredited and EPA recognized Certification Body, in accordance with SRCC OG-100, Operating Guidelines and Minimum Standards for Certifying Solar Collectors, and has been certified by the SRCC. This award of certification is subject to all terms and conditions of the Program Agreement and the documents incorporated therein by reference. This document must be reproduced in its entirety.

ADDITIONAL INFORMATION (click here to return to the rating page)			
Test Lab:	Forschungs- und Testzentrum für Solaranlagen (TZS) am Institut für Thermodynamik und Wärmetechnik (ITW) der Universität Stuttgart	Test Date:	April 11, 2011
Test Report Number:	10COL932S	Test Location:	

SOLAR COLLECTOR CONSTRUCTION DETAILS					
Gross Length:	1.893 m	Gross Width:	1.183 m	Gross Depth:	103.000 mm

COLLECTOR MATERIALS					
Outer Cover:	Glass sheet	Enclosure back:	Aluminum	Back Insulation:	Fiber, None
Inner Cover:	None	Enclosure side:	Aluminum	Side Insulation:	Fiber, None
Absorber Description:		Flow Pattern:			
Riser Tube:	Copper	Fin:			
Absorber Coating:	Selective	Tube to fin connection			

GLAZING	Outer Cover	Inner Cover
Material:	Glass sheet	None
Surface Characteristics:		
Thickness:	4.0 mm	N/A
Transmissivity:		
Length:	1.842 m	
Width:	1.131 m	
Tube Glazing to Header Enclosure Seal:	EPDM gasket	

ABSORBER:		Absorber Coating:		Selective	
Header Material:		Header OD:		Header Wall:	
Riser Tube Material:	Copper	Riser Tube OD:		Riser Tube Wall Thickness:	
Fin Material:		Fin Thickness:	0.40 mm		





CERTIFIED SOLAR COLLECTOR

SUPPLIER:
Dimas SA
 2nd KLM Argos-Nafplion
 Argos, 21200 Greece
 www.dimas-solar.gr
 In Accordance with:
SRCC Standard 100-2010-08

BRAND: Dimas SA
MODEL: SOL+23
COLLECTOR TYPE: Glazed Flat Plate
CERTIFICATION #: 2011077C
Original Certification: October 19, 2011
Expiration Date: April 11, 2023

The solar collector listed below has been evaluated by the Solar Rating & Certification Corporation™ (SRCC™), an ISO/IEC 17065 accredited and EPA recognized Certification Body, in accordance with SRCC OG-100, Operating Guidelines and Minimum Standards for Certifying Solar Collectors, and has been certified by the SRCC. This award of certification is subject to all terms and conditions of the Program Agreement and the documents incorporated therein by reference. This document must be reproduced in its entirety.

Flow Pattern:					
Number of Riser Tubes:	10	Tube Spacing:		Number of times each riser crosses the absorber:	10
Length of Flow Path:	1.78 m	Riser to Fin/Plate Bond:			

INSULATION:					
Location	Type	Thickness	Location	Type	Thickness
Back – Top Layer:	Fiber		Sides – Inner Layer:	Fiber	
Back – Bottom Layer:	None		Sides – Outer Layer:	None	
Enclosure Fastening Methods:					

Power Output per Collector(W) [Ti-Ta, G = 1000 W/m²]				
0	10	30	50	70

PRESSURE DROP				
Flow	ΔP		Flow	ΔP
ml/s	Pa		gpm	in H₂O
20			0.32	
50			0.79	
80			1.27	

